







PROFILES H3 PRE-PRIMED

NSW

BOARDS



FASCIAS

BULLNOSE 138mm x 18mm



BULLNOSE 180mm x 18mm



BULLNOSE 180mm x 25mm



HAND RAILS & BOTTOM RAILS

BOTTOM RAIL BR2
65mm x 30mm



BOTTOM RAIL BR16
88mm x 42mm



BOTTOM RAIL
88mm x 30mm



HAND RAIL HR1 DR
63mm x 65mm



HAND RAIL HR5
88mm x 42mm



HAND RAIL HR6 DR
88mm x 42mm



HAND RAIL HR8 DR
79mm x 63mm



LINING

TGV PATTERN 302 138mm x 11mm



TGV 90mm x 18mm



TGV PATTERN 302 138mm x 18mm



TGV PATTERN 321 138mm x 11mm



TGV REBATED PATTERN 412 138mm x 18mm



BEAMS

GL10
140mm x 65mm



GL10
180mm x 65mm



GL10
240mm x 65mm



GL10
290mm x 65mm



POSTS

GL8 2mm
Round Corners
63mm x 63mm



GL8 2mm
Round Corners
88mm x 63mm



GL8 2mm
Round Corners
135mm x 135mm



GL8 2mm
Round Corners
185mm x 185mm



GL8 2mm
Round Corners
88mm x 88mm



GL8 2mm
Round Corners
112mm x 112mm



CLADDING

CHAMFER 166mm x 18mm



WEATHERBOARD CLASSIC REBATED BEVELBACK 138mm x 18mm



WEATHERBOARD CLASSIC REBATED BEVELBACK 185mm x 18mm



WEATHERBOARD RUSTICATED 185mm x 18mm



WEATHERBOARD RUSTICATED 138mm x 18mm



DOOR JAMBS

SINGLE 138mm x 30mm



DOUBLE 163mm x 30mm



MOULDINGS

QUAD
18mm



SCOTIA
30mm x 30mm



QUAD
23mm




EXTERNAL CORNER MOULD
42mm x 42mm



Why choose Claymark Tru-Pine?

- ✓ Strong and durable
- ✓ H3 Hazard Class Protection
- ✓ Pre-Primed
- ✓ Defect free
- ✓ Strict quality control
- ✓ Proven history
- ✓ Plantation pine

Premium quality timber ideal for above ground, outdoor use, structurally graded, smooth, dressed finish for easy painting. Available in an extensive range of sizes. The perfect finish for your outdoor living.



**PROUDLY
DISTRIBUTED BY**



Ingrained Precision

in everything we do

Usage

Claymark Tru-Pine is a premium exterior treated timber for above ground use only. Ensure a timber clearance of 100mm above paved surfaces or 175mm above finished ground level is maintained.

Treatment

Claymark Tru-Pine achieves a H3 Hazard Class protection rating through treatment with an advanced organic treatment using LOSP (Light Organic Solvent Preservative) that protects against fungal decay and insect attack.

Fittings

Use hot-dip galvanised nails, screws, bolts and brackets in general locations. For coastal conditions subject to sea spray use stainless steel.

Sealing

During the installation process all exposed unprimed surfaces resulting from cut ends, mitres, notching, boring, punched nail holes or similar should be resealed with a suitable acrylic or oil-based premium exterior timber primer.

Painting Specification

1. Spot prime and putty all nail holes.
2. Ensure primed surfaces are clean and free from contaminants such as dust, grease or mildew.
3. Apply a minimum of two full coats of premium acrylic exterior house paint to recommended film thickness

For a better finish and extended paint durability we recommend the application of one full coat of premium quality OIL BASED primer undercoat.

Use colours that have a Light Reflective Value (LRV) of 45 to 100 (100 being pure white). Colours with a LRV of 44 to 0 (0 being pure black) progressively generate extreme surface heat when exposed to direct sunlight and can cause resin bleed, shrinkage, distortion and cracking. It will also reduce the service life of the paint coatings.

Storage

Store the product in a dry environment away from damp ground until use. Kiln-dried Radiata Pine timber is hygroscopic and will absorb moisture in a damp environment and release it in a dry environment. If timber absorbs moisture, some dimensional swelling will occur.

Health & Safety

Tru-Pine treated products are safe to handle using normal timber handling precautions.

Technical Data & Installation Guide

Please refer to the Building Code of Australia guidelines or your local building authority/council to ensure correct construction practices are followed.

Tru-Pine meets Service Class 3/AS5068 standards for structural products.

Visit www.claymark.co.nz for technical specifications, product information guides, span tables, application guides and warranties.